

**To / 致:**

Company / 公司: Shenzhen Qiming Photovoltaic Technology Co., Ltd.

Contact / 联系人: Mr. Lu Bo

Email / 邮箱: 1757356@skyworth.com

**From / 自:**

Company / 公司:

TÜV NORD (HANGZHOU)  
CO., LTD. / 杭州汉德质量认证  
服务有限公司

Contact / 联系人:

Mrs. Serena.Wu / 郭玉婷 女士

Email / 邮箱:

sewu@tuv-nord.com

**Subject: Announcement of cancellation****主题: 证书取消通知**

File No.: PVP04156/25C-02

项目号:

License holder: Shenzhen Qiming Photovoltaic Technology Co., Ltd.

持证人:

Certificate No.: 44 780 24 406749 - 487R3A1M5

证书号:

Product: Crystalline Silicon Terrestrial Photovoltaic (PV) Modules

产品: 地面用晶体硅光伏组件

Herewith it is declared, that the above noted certificate(s) has (have) been invalidated since 2025-07-11  
特此声明, 上述证书自 2025 年 7 月 11 日起失效。

The cancellation is due to:

取消原因:

☐ License holder applied for cancellation.

持证人申请取消。

☒ New certificate(s) (no: 44 780 24 406749 - 487R4A1M6) has (have) been issued to replace the cancelled one(s).

新证书 (证书号: \_\_44 780 24 406749 - 487R4A1M6\_\_) 签发, 取代旧证书。

☐ Certificate(s) is (are) expired.

证书有效期至。

☐ Certificate(s) has (have) been suspended for one year, and the factory inspection, verification, and rectification required to restore the certificate(s) has (have) not been completed.

证书暂停满一年, 未完成恢复证书所需厂检、核查、整改等。

☐ Certificate(s) has (have) been suspended for one year, and the annual certificate fee has (have) not been paid.

证书暂停满一年, 未支付证书年费。

☐ Others: \_\_\_\_\_

其他情况: \_\_\_\_\_

Please pay attention to stop using the invalid certificate(s) from 2025-07-11 Meanwhile, please send back the original copies of above mentioned certificate(s) to us.

请注意从 2025 年 7 月 11 日开始停止使用无效证书。同时，请将上述证书原件寄回给我们。

TÜV NORD reserved the right of final explanation about the cancellation of certificate(s). TÜV NORD will not take any responsibility for the circumstance of misusing the invalid certificate(s) by the license holder or the manufacturer.

TÜV NORD 保留对证书取消的最终解释权。TÜV NORD 对证书持有者或制造商滥用无效证书的情况不承担任何责任。

Renewable Energy / 可再生能源

TÜV NORD (Hangzhou) Co., Ltd. / 杭州汉德质量认证服务有限公司



Serena.Wu / 鄢玉婷

Technical Support / 技术支持

# CERTIFICATE

**TÜV NORD CERT GmbH**

herewith declares that

**Shenzhen Qiming Photovoltaic Technology Co., Ltd.**

201, Building 10, No. 2-1, Xiguangyue Third Road, Loucun Community, Xinhua Street, Guangming District, Shenzhen

is authorized to provide the product mentioned below with the mark as illustrated:

**Description of product (details see Annex 2):**

**Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**



Valid from: 2025-07-11

Valid until: 2029-12-19

Certification program:

P12-VA-01 Rev. 17 09.20

Certification fundamental(s):

IEC 61215-1:2021 / EN IEC 61215-1:2021;  
IEC 61215-1-1:2021 / EN IEC 61215-1-1:2021;  
IEC 61215-2:2021 / EN IEC 61215-2:2021;  
IEC 61730-1:2023;  
IEC 61730-2:2023.

Registered No.:

44 780 24 406749 - 487R4A1M6

Manufacturer and factory(-ies):

See Annex 1

Test Report No.:

492013492.007

File No.:

PVP02145/25P-02



**TÜV NORD CERT GmbH**  
**Certification Body**  
**Consumer Products**



Essen, 2025-07-11

Please also pay attention to the information stated overleaf.

Anlage 1 zum Zertifikat Nr.: / Annex 1 to Certificate No.: 44 780 24 406749 - 487R4A1M6

Seite / Page 1 von / of 1

Aktenzeichen: / File reference: PVP02145/25P-02

2025-07-11

**Manufacturer and factory(-ies):**

Manufacturer: **Shenzhen Qiming Photovoltaic Technology Co., Ltd.**  
201, Building 10, No. 2-1, Xiguangyue Third Road, Loucun Community,  
Xinhu Street, Guangming District, Shenzhen

Factory: **Shenzhen Qiming Photovoltaic Technology Co., Ltd.**  
201, Building 10, No. 2-1, Xiguangyue Third Road, Loucun Community,  
Xinhu Street, Guangming District, Shenzhen

Factory inspection report no.: 862010909.002

**Remark:**

Factory inspection is mandatory to be performed annually. Please refer to factory inspection report for detailed information.



**TÜV NORD CERT GmbH**  
**Certification Body**  
**Consumer Products**

## Description of product(s):

|                                                           |                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Module types:                                             | <b>Double Glass PV Modules with Half-cut 182mm PERC Mono-crystalline Silicon Solar Cells:</b><br>144 cells: QM182PHCD-xxx-72 (xxx = 545 - 565, in steps of 5)<br>120 cells: QM182PHCD-xxx-60 (xxx = 455 - 470, in steps of 5)<br>108 cells: QM182PHCD-xxx-54 (xxx = 410 - 420, in steps of 5)<br>Remark: xxx indicates rated output power generated from front side only at STC. |
| Maximum system voltage:                                   | 1500V                                                                                                                                                                                                                                                                                                                                                                            |
| Maximum overcurrent protection rating:                    | 25A                                                                                                                                                                                                                                                                                                                                                                              |
| Electrical protection class:                              | Class II                                                                                                                                                                                                                                                                                                                                                                         |
| Pollution degree:                                         | 1                                                                                                                                                                                                                                                                                                                                                                                |
| 98th percentile module operating temperature ( $T_{98}$ ) | 70°C                                                                                                                                                                                                                                                                                                                                                                             |
| Design load (positive / negative):                        | 3600Pa / 2400Pa                                                                                                                                                                                                                                                                                                                                                                  |
| Safety factors:                                           | 1.5                                                                                                                                                                                                                                                                                                                                                                              |
| Fire safety class:                                        | Class C according to UL790                                                                                                                                                                                                                                                                                                                                                       |

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Module types: | <b>Double Glass PV Modules with Half-cut 182 mm series TOPCon Mono-crystalline Silicon Solar Cells:</b><br>156 cells: QM182THCD-xxx-78 (xxx = 610 - 650, in steps of 5)<br>156 cells: QM182THCDQ-xxx-78 (xxx = 615 - 650, in steps of 5)<br>156 cells: QM182THCDZ-xxx-78 (xxx = 615 - 650, in steps of 5)<br>144 cells: QM182THCD-xxx-72 (xxx = 565 - 595, in steps of 5)<br>144 cells: QM182THCDQ-xxx-72 (xxx = 570 - 595, in steps of 5)<br>144 cells: QM182THCDZ-xxx-72 (xxx = 570 - 595, in steps of 5)<br>120 cells: QM182THCD-xxx-60 (xxx = 470 - 495, in steps of 5)<br>120 cells: QM182THCDQ-xxx-60 (xxx = 475 - 495, in steps of 5)<br>120 cells: QM182THCDZ-xxx-60 (xxx = 475 - 495, in steps of 5)<br>108 cells: QM182THCD-xxx-54 (xxx = 425 - 450, in steps of 5)<br>108 cells: QM182THCDQ-xxx-54 (xxx = 425 - 445, in steps of 5)<br>108 cells: QM182THCDZ-xxx-54 (xxx = 425 - 445, in steps of 5)<br>28 cells: QM182THCDW-xxx-14 (xxx=105-110, in steps of 5)<br>16 cells: QM182THCDW-xxx-8 (xxx=60)<br>8 cells: QM182THCDW-xxx-4 (xxx=30)<br>Remark: xxx indicates rated output power generated from front side only at STC. |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|



**TÜV NORD CERT GmbH**  
**Certification Body**  
**Consumer Products**

|                                                                 |                                                              |
|-----------------------------------------------------------------|--------------------------------------------------------------|
| Maximum system voltage:                                         | 1500V                                                        |
| Maximum overcurrent protection rating:                          | 30A or 25A, refer to CDF for details                         |
| Electrical protection class:                                    | Class II                                                     |
| Pollution degree:                                               | 1                                                            |
| 98th percentile module operating temperature (T <sub>98</sub> ) | 70°C                                                         |
| Design load (positive / negative):                              | 3600Pa / 2400Pa or 3600Pa / 1600Pa, refer to CDF for details |
| Safety factors:                                                 | 1.5                                                          |
| Fire safety class:                                              | Class C according to UL790                                   |

Module types:

**Colourful Double Glass PV Modules with Half-cut 182 mm series TOPCon Mono-crystalline Silicon Solar Cells:**

156 cells: QM182THCDC-xxx-78 (xxx=350-375, 410-445, 465-500, 540-560, in steps of 5)

144 cells: QM182THCDC-xxx-72 (xxx=325-345, 380-410, 435-460, 500-515, in steps of 5)

120 cells: QM182THCDC-xxx-60 (xxx=270-285, 315-340, 360-385, 415-430, in steps of 5)

108 cells: QM182THCDC-xxx-54 (xxx=245-260, 285-305, 320-345, 375-385, in steps of 5)

Remark: xxx indicates rated output power generated from front side only at STC.

|                                                                 |                            |
|-----------------------------------------------------------------|----------------------------|
| Maximum system voltage:                                         | 1500V                      |
| Maximum overcurrent protection rating:                          | 25A                        |
| Electrical protection class:                                    | Class II                   |
| Pollution degree:                                               | 1                          |
| 98th percentile module operating temperature (T <sub>98</sub> ) | 70°C                       |
| Design load (positive / negative):                              | 3600Pa / 1600Pa            |
| Safety factors:                                                 | 1.5                        |
| Fire safety class:                                              | Class C according to UL790 |



**TÜV NORD CERT GmbH**  
**Certification Body**  
**Consumer Products**

|                                                                 |                                                                                                                                                                                                                         |
|-----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Module types:                                                   | <b>Double Glass PV Modules with Half-cut 210mm TOPCon Mono-crystalline Silicon Solar Cells:</b><br>132 cells: QM210THCD-xxx-66 (xxx=695-720, in steps of 5)<br>120 cells: QM210THCD-xxx-60 (xxx=630-655, in steps of 5) |
| Maximum system voltage:                                         | 1500V                                                                                                                                                                                                                   |
| Maximum overcurrent protection rating:                          | 30A                                                                                                                                                                                                                     |
| Electrical protection class:                                    | Class II                                                                                                                                                                                                                |
| Pollution degree:                                               | 1                                                                                                                                                                                                                       |
| 98th percentile module operating temperature (T <sub>98</sub> ) | 70°C                                                                                                                                                                                                                    |
| Design load (positive / negative):                              | 3600Pa / 1600Pa                                                                                                                                                                                                         |
| Safety factors:                                                 | 1.5                                                                                                                                                                                                                     |
| Fire safety class:                                              | Class C according to UL790                                                                                                                                                                                              |

|                                                                 |                                                                                                                                                                                                                                                                                                                                                      |
|-----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Module types:                                                   | <b>Double Glass PV Modules with Half-cut 210mmx182mm TOPCon Mono-crystalline Silicon Solar Cells:</b><br>132 cells: QM210THCD-xxx-66 (xxx=605-630, in steps of 5)<br>120 cells: QM210THCD-xxx-60 (xxx=550-570, in steps of 5)<br>108 cells: QM210THCD-xxx-54 (xxx=495-510, in steps of 5)<br>96 cells: QM210THCD-xxx-48 (xxx=440-455, in steps of 5) |
| Maximum system voltage:                                         | 1500V                                                                                                                                                                                                                                                                                                                                                |
| Maximum overcurrent protection rating:                          | 25A                                                                                                                                                                                                                                                                                                                                                  |
| Electrical protection class:                                    | Class II                                                                                                                                                                                                                                                                                                                                             |
| Pollution degree:                                               | 1                                                                                                                                                                                                                                                                                                                                                    |
| 98th percentile module operating temperature (T <sub>98</sub> ) | 70°C                                                                                                                                                                                                                                                                                                                                                 |
| Design load (positive / negative):                              | 3600Pa / 1600Pa                                                                                                                                                                                                                                                                                                                                      |
| Safety factors:                                                 | 1.5                                                                                                                                                                                                                                                                                                                                                  |
| Fire safety class:                                              | Class C according to UL790                                                                                                                                                                                                                                                                                                                           |

Remark:

For detailed product information, please refer to CDF (Constructional Data Form) attached to test report with same file no.



**TÜV NORD CERT GmbH**  
Certification Body  
Consumer Products